

BOX PALLETIZER

HY-D-FLEX^{MD}
PALLETIZER

OPTIONS

DATA SHEET

WEB SITE

PRESENTATION

The box palletizer is available in various forms which covers a wide variety of applications for **patterns, speed** and type of **format**.

Picking up and depositing boxes from the bottom produces **safer and seamless handling** without affecting box closing quality. The box palletizer is equipped according to the gripper requirements; capable of handling one or more boxes.

The box palletizer production capacity can reach up to 60 boxes per minute and speed can be increased by adding a second robot to the cell.

FEATURES & ADVANTAGES

- Picking up boxes supporting the bottom ensures **100% safe handling**.
- Removal of damaged product.
- Complete automation from palletizing to the final pallet, reducing **unnecessary handling** or **maneuvering** of pallets.
- Easy pattern programming.
- Wide variety of configurations and options possible.
- High energy efficiency.
- Production speed: up to **60 boxes/min**.

BOX PALLETIZER

HIGH PERFORMANCE SOLUTION

In order to obtain a complete solution, additional options can be integrated to the end of the production line preparing your pallet for storing or shipping.



OPTIONS

- Integrated wrapping (top or slip sheet).
- Plastic on pallet.
- Corner protectors.
- Box or pallet labeling.
- Box printing.
- Weigher.

DATA SHEET

Robot:	ABB IRB 460 - 660
Speed:	Maximum capacity 60 boxes per minute / robot
Gripper:	Mechanical, 1 box multiple gripping
Feeding:	1 to 4 lines maximum per production
Power supply:	575 VAC & 120 V/1/60 15A.
Construction:	Painted steel - (stainless steel option)
Temperature:	Between +4°C à +50°C
Configuration:	Variety of configurations available Dimensions: 28' x 32' (8.5m x 9.7m).